



Material Safety Data Sheet

 Yazell Fluids LLC
 Emergency:
 (806) 674-5099

 7705 Pinnacle Dr.
 Information:
 (806) 418-2516

 Amarillo, TX
 Fax:
 (806) 418-2517

 79119
 Revision Date:
 04/15/2013

SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

General Product Name: BioGreen UltraGard Machine Degreaser

Synonyms: None

Product Description: Cleaner/degreaser

Manufacturer: Yazell Fluids LLC

SECTION 2: COMPOSITION / INFORMATION ON INGREDIENTS

This product contains no hazardous materials.

SECTION 3: HAZARD IDENTIFICATION

Potential Health Effects

Inhalation: Negligible unless heated to produce vapors. Vapors or finely misted

materials may irritate the mucous membranes and cause irritation,

dizziness, and nausea. Remove to fresh air.

Eye Contact: May cause irritation. Irrigate eye with water for at least 15 to 20

minutes. Seek medical attention if symptoms persist.

Skin Contact: Prolonged or repeated contact is not likely to cause significant skin

irritation. Material is sometimes encountered at elevated

temperatures. Thermal burns are possible.

Ingestion: No hazards anticipated from ingestion incidental to industrial

exposure.





SECTION 4: FIRST AID MEASURES

Eye Contact: Irrigate eyes with a heavy stream of water for at least 15 to 20

minutes.

Skin Contact: Wash exposed areas of the body with soap and water.

Inhalation: Remove from area of exposure; seek medical attention if symptoms

persist.

Ingestion: Give one or two glasses of water to drink. If gas-intestinal

symptoms develop, consult medical personnel. (Never give

anything by mouth to an unconscious person)

SECTION 5: FIRE FIGHTING MEASURES

Flash Point (Method Used): >200C/392F (ASTM 93)

Flammability Limits: None known

Extinguishing Media: Dry chemical foam, halon, CO2, water spray (fog). Water stream

may splash the burning liquid and spread fire.

Special Fire Fighting

Procedures:

Use water spray to cool drums exposed to fire.

Unusual Fire and
Oil soaked rags can cause spontaneous combustion if not handled properly. Before disposal, wash rags with soap and

water and dry in well ventilated area. Firefighters should use selfcontained breathing apparatus to avoid exposure to smoke and

vapor.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Remove sources of ignition, contain spill to smallest area possible. Stop leak if possible. Pick up small spills with absorbent materials such as paper towels, "Oil Dry", sand or dirt. Recover large spills for salvage or disposal. Wash hard surfaces with safety solvent or detergent to remove remaining oil film. Grease nature will result in a slippery surface.

SECTION 7: HANDLING AND STORAGE

Store in closed containers between 50 degrees F and 120 Degrees F.

Keep away from oxidizing agents, excessive heat, and ignition sources.

Store and use in well ventilated areas.

Do not store or use near heat, spark, or flame, store out of sun.

Do not puncture, drag, or slide this container.

Drum is not a pressure vessel; never use pressure to empty.





SECTION 8: EXPOSURE CONTROL AND PERSONAL PROTECTION

Respiratory Protection: If vapors or mists are generated, wear a NIOSH approved organic

vapor/mist/respirator.

Protective Clothing: Safety glasses, goggles, or face shield recommended to protect eyes

from mists or splashing. Use PVC coated gloves if known/suspect

sensitivity exists.

Other Protective

Measures:

Employees must practice good personal hygiene, washing exposed

areas of skin several times daily and laundering contaminated

clothing before re-use.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Flash Point: >200C/392F

Upper Flammable Limit:
Lower Flammable Limit:
Not evaluated

Specific Gravity: 0.86

Bulk Density: Not evaluated

Water Solubility: Soluble

Percent volatile: Not evaluated

Volatile Organic Compound: Not evaluated

Vapor Density (air = 1): >1 Evaporation Rate (butyl <1

acetate=1):

. . . .

Odor: Mild

Appearance: Clear to pale yellow fluid

Viscosity: Not evaluated

Odor Threshold: Not evaluated

Boiling Point (@760mmHg): >200C





SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Pour Point Temperature: 12C/54F

SECTION 10: STABILITY AND REACTIVITY

General: This product is stable and hazardous polymerization will not occur.

Incompatible Materials &

Conditions to Avoid:

Strong oxidizing agents

Hazardous Decomposition Combustion produces carbon monoxide, carbon dioxide along

Products: with thick smoke.

SECTION 11: DISPOSAL CONSIDERATIONS

Waste Disposal: Waste may be disposed of by a licensed waste disposal company.

Contaminated absorbent material may be disposed of in an approved

landfill. Follow local, state, and federal disposal regulations.

SECTION 12: TRANSPORTATION INFORMATION

IATA (Air): Not regulated US DOT (Land): Not regulated

IMO (Water): Additional information required prior to transport

SECTION 13: REGULATORY INFORMATION

OSHA Status: This product is not hazardous under criteria of the Federal

OSHA Hazard Communication Standard 29 CFR 1910.1200. However, thermal processing and

decomposition fumes from this product may be hazardous

as noted in Sections 2 and 3.

TSCA Status: This product is listed on TSCA.

CERCLA NOT reportable.

(Comprehensive Response Compensation & Liability Act):

SARA TITLE III (Super Amendments & Reauthorization Act)

Section 312 Extremely

Hazardous Substances:

None

Section 311/312 Hazard

Non-hazardous under section 311/312

Categories:





SECTION 13: REGULATORY INFORMATION

Section 313 Toxic Chemicals: None

RCRA Status: If discarded in its purchased form, this product would not

be hazardous waste either by listing or by characteristic. However, under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste,

(40 CFR 261.20-24)

California Proposition 65: The following statement is made in order to comply with

the California Safe Drinking Water and Toxic Enforcement Act of 1986. This product contains no chemicals known

to the state of California to cause cancer.

SECTION 14: OTHER INFORMATION

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. Such information is to the best of the company's knowledge and believes accurate and reliable as of the date indicated. However, no representation, warranty or guarantee of any kind, express or implied, is made as to its accuracy, reliability or completeness and we assume no responsibility of any loss, damage or expenses, direct or consequential, arising out of use. It is the user's responsibility to satisfy himself as to the suitableness and completeness of such information for the own particular use.